## **EUROPEAN PATENT OFFIC**

## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

2002372668

**PUBLICATION DATE** 

26-12-02

APPLICATION DATE **APPLICATION NUMBER**  14-06-01 2001179579

APPLICANT: NIKON CORP;

**INVENTOR:** 

TAKAHASHI YUTO: 1

INT.CL.

G02B 17/08 G02B 13/14 G02B 13/18


G03F 7/20 H01L 21/027

TITLE

CATADIOPTRIC SYSTEM AND

**EXPOSURE DEVICE HAVING THIS** 

CATADIOPTRIC SYSTEM



ABSTRACT :

PROBLEM TO BE SOLVED: To provide a catadioptric system which is small in the distance be tween on object surface and an image surface, has simple constitution of a small number of lens elements, is capable of achieving high resolution of  $\leq$ 0.1  $\mu m$  by using light of a vacuum UV wavelength of, for example, ≤180 nm.

SOLUTION: This catadioptric system has a first imaging optical system (G1) which has a concave mirror (CM2) and a plane reflecting mirror (M1) and forms the first intermediate image of the first surface in accordance with the light from the first surface (R), a second imaging optical system (G2) which has a concave mirror (CM3) and a plane reflecting mirror (M4) and forms the second intermediate image of the first surface in accordance with the light through the first imaging optical system and the third imaging optical system (G3) of a refraction type which forms the final image of the first surface on the second surface (W) in accordance with the light through the second imaging optical system.

COPYRIGHT: (C)2003,JPO